



## VEHICLE DESCRIPTION

HME HAF51T 1871-SFO-MFD 96" Wide Flat Roof Custom 4x2 4-Door Chassis  
49,740lbs GVWR • 1500 GPM Side Mount Pump • 500 Gallon Tank • Stainless Body 22953

## STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

### DRIVETRAIN:

Cummins ISL9-370hp EPA13 Engine  
Cummins Engine Brake  
Allison 3000EVS 5-speed, Push Button Select Transmission  
18,740lbs Front Axle  
31,000lbs Single Rear Axle  
Dual Air Brake System / Bendix AD SP Dryer  
S-cam Front and Rear Brakes  
Goodyear 315/80R22.5-20PR (L) Front - G291 - 18,180#-19,450  
Goodyear 315/80R22.5-20PR (L) Rear - G291 - 31,000#  
50 Gallon Fuel Tank

### EXTERIOR:

Flat Roof  
Exterior Grab Handles - 24" Long  
Heated and Remote Controlled Moto-Mirror with Lower Convex  
Dark Gray-Lite Door Glass - Crew Side Doors  
Exterior Rear Wall – Diamond Plate Overlay  
Cab Ground Lights - LED Strip Lights  
Cab Tilt - Electric Pump / Cab Tilt Road Interlock  
10" high Bumper with a 21" Extension and Chrome Tow Hooks  
Dual Stutter Tone Air Horns - Bumper Recessed  
Whelen Electric Siren with Two Recessed Mntd 100Watt Siren Speaker  
Q2B Mechanical Siren - Gravelshield Mtd - Driver's Side

### INTERIOR:

Driver's Pos - Highback Air-Ride Suspension, HO Bostrom Sierra-50 Seat  
Officer's Pos - Fixed Mounting - HO Bostrom - Tanker 300CT  
Two (2) Fwd Facing, Flip Down NO SCBA Seats  
Two (2) Rear Facing Fixed Bottom SCBA, HO Bostrom - Tanker 300CT  
45,000 BTU, Single Condenser AC/ Heater & 36,000 BTU Suppl. Heater  
Apparatus Base Digital Electrical System - Class1 EsKey  
Overhead SPS Panel - EsKey

### PUMP:

47" Side Mount Pump Enclosure  
Hale "Q-Max" - 1500GPM Rating  
Mechanical Seal / Intake & Discharge Anode/ Class 1 Master Drain  
Right/Left Side 6" Steamer Inlets / Left Side 2.5" Inlet  
4.0" Rear Aerial Waterway Inlet  
2.5"/2.5" Left Side Discharges & 2.5"/3.0" Right Side Discharges  
Two (2) 1.5" Single Stack / One (1) 2.5" Double Crosslay  
3.0" Tank to Pump with 3.0" Ball Valve

### BODY:

Stainless Steel Body / Brushed Stainless Steel Compartment Roof  
Stainless Steel Wheel Liners  
182ft<sup>3</sup> of Compartment Storage/ 31ft<sup>3</sup> Hosebed  
Hydraulic Ladder Rack  
Satin Anodized Roll-up Compartment Doors  
Body Rear "Out and Down" Turntable/Hosebed Access Ladder  
Seven (7) SCBA Storage Compartments  
Trays, Shelves, and Toolboards

### LIGHTING:

Whelen Warning Light Package  
Federal Signal Turn Signals  
Whelen LED Stop/Tail/Backup Lighting  
Whelen LED OS Series ICC Lighting - Custom Cab and Body

### AERIAL:

51' Two-Section Ladder with Joystick Control  
Elkhart Cobra, Electric Monitor  
Performance Capabilities, 51' Tower, 1250GPM, -10/+75

## OPTIONAL EQUIPMENT

Double Frame Rails  
Front and Rear Aluminum Wheels  
Two-Tone Cab Exterior Paint  
22.5" x 9.00" Polished Aluminum Front Wheels  
22.5" x 9.00" Inner and Outer Polished Aluminum Rear Wheels  
Wheel Bright Finish Protection  
ABS Mud & Snow Selector Switch  
320 Amp Alternator - Leece-Neville  
Wire Braided Fuel Lines  
Kussmaul - 091-9-1200 Pump Plus - Comp & 40A Charger  
Kussmaul 20 AMP - 120v - Super Auto Eject  
Back-Up Camera System, Wireless Camera with Garmin GPS  
AM/FM Stereo CD/Weather Band Radio w/Four Speakers  
Rear Wall Windows - Fixed Glass  
Electric Windows - Four Doors - Driver Additional Controls  
Center Tool Storage Area - Hydraulic Rescue Tool Storage - Diamond Plate Cover  
Q2B Mechanical Siren - Gravelshield Mtd - Driver's Side  
LED Strip Lights, Armor Guard, Runningboard, Pumphouse  
Harrison 8KW Generator  
Hannay Cable Reel  
Dust Shields - Single Rear Axle

**TOTAL** SEE A SALES REPRESENTATIVE

## SOLD TO

Stock Inventory

## METHOD OF TRANSPORTATION

Drive-Away

## FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

## VIN

www.firetruck.com



HME, Incorporated - Wyoming