



VEHICLE DESCRIPTION

HME HAF51T 1871-SFO-MFD 96” Wide Flat Roof Custom 4x2 4-Door Chassis
49,180 lbs. GVWR • 1250 GPM Side Mount Pump • 500 Gallon Tank • Stainless Body 22954

OPTIONAL EQUIPMENT

Double Frame Rails
Front and Rear Aluminum Wheels
Two-Tone Cab Exterior Paint

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

DRIVETRAIN:

Cummins ISL9-370hp EPA13 Engine
Cummins Engine Brake
Allison 3000EVS 5-speed, Push Button Select Transmission
Dual Air Brake System / Bendix AD SP Dryer
S-cam Front and Rear Brakes
Goodyear 315/80R22.5-20PR (L) Front - G291 - 18,180#
Goodyear 315/80R22.5-20PR (L) Rear - G291 - 31,000#
22.5" x 9.00" Polished Aluminum Front Wheels
22.5" x 9.00" Inner and Outer Polished Aluminum Rear Wheels
50 Gallon Fuel Tank
270 Amp Alternator - Leece-Neville

EXTERIOR:

Exterior Grab Handles - 24" Long
Heated and Remote Controlled Moto-Mirror with Lower Convex
Dark Gray-Lite Door Glass - Crew Side Doors
Exterior Rear Wall – Diamond Plate Overlay
Cab Ground Lights - LED Strip Lights
Cab Tilt - Electric Pump / Cab Tilt Road Interlock
10" high Bumper and a 21" Extension w/Chrome Tow Hooks
Dual Stutter Tone Air Horns - Bumper Recessed
Whelen Electric Siren with Two Recessed Mtd. 100 Watt Siren Speaker

INTERIOR:

Driver's Pos. - Highback Air-Ride Suspension, HO Bostrom Sierra-50 Seat.
Officer's Pos. - Fixed Mounting – HO Bostrom – Tanker 300CT
Two (2) Fwd. Facing, Flip Down NO SCBA, Seats
Two (2) Fwd. Facing, Fixed Bottom SCBA, HO Bostrom – Tanker 300CT
57,600 BTU Heater Mtd. Above The Windshield
45,000 BTU, Single Condenser AC/Heater
36,000 BTU Supplemental Auxiliary Heater
Apparatus Base Digital Electrical System – Class 1 EsKey
Overhead SPS Panel - EsKey

PUMP:

47" Side Mount Pump Enclosure
Hale "Q-Flo Plus" – 1250 GPM
Mechanical Seal / Intake & Discharge Anode/ Class 1 Master Drain
Right/Left Side 6" Steamer Inlets / Left Side 2.5" Inlet
4.0" Rear Aerial Waterway Inlet
Two (2) 2.5" Left Side Discharges / Two (2) 2.5" Right Side Discharges
Two (2) 1.5" Single Stack / One (1) 2.5" Double Crosslay
3.0" Tank to Pump with 3.0" Ball Valve

BODY:

Stainless Steel Body / Stainless Steel Compartment Roof
Stainless Steel Fenderettes Wheel Liners
182ft³ of Compartment Storage/ 31ft³ Hosebed
Hydraulic Ladder Rack
Satin Anodized Roll-up Compartment Doors
Body Rear "Out and Down" Turntable/Hosebed Access Ladder
Seven (7) SCBA Storage Compartments

LIGHTING:

PowerArc Dual Volt Series Light Bar
PowerArc LED210 Lighting – Cab & Body
Federal Signal Turn Signals
Whelen LED Stop/Tail/Backup Lighting
Whelen LED OS Series ICC Lighting – Custom Cab and Body

AERIAL:

51' Two Section Rear Mount Water Tower w/Joystick Controls
Elkhart Cobra Electric Monitor
Electronically Controlled Elkhart Nozzle
Performance Capabilities, 51' Tower, 1250GPM, -10/+75

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

VIN

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

www.firetruck.com



HME, Incorporated – Wyoming