



VEHICLE DESCRIPTION

HME 1871 SFO SilverFox 4x2 4-Door Custom Chassis

45,180lbs GVWR • 1500 GPM Side Mount Pump • 1000 Gallon Water Tank • Stainless Body 22957

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

DRIVETRAIN:

Cummins ISL9 370hp EPA13 Engine
Allison 3000EVS Automatic Transmission
Engine Brake
S-Cam Front and Rear Brakes
Goodyear 315/80R22.5-20PR (L) Front - G291 - 18,180#
Goodyear 12R22.5-16PR (H) Rear M&S - G182 - 27,000#
270 Amp Leece-Neville Alternator
50 Gallon Fuel Tank

EXTERIOR:

Four (4) Door Custom SFO-MFD Cab with 12" Raised Roof
18,180LBS GAWR Front Axle
27,000LBS GAWR Rear Axle
3-Dimensional Stainless Front Grille
Heated and Remote Controlled Moto-Mirror with Lower Convex
Cab Ground Lights - LED
21" Front Bumper Extension / Front Tow hooks
Dual Stutter Tone Air Horns - Bumper Recessed
Whelen Electronic Siren - Model 295SLSA1
Two (2) Cast Products, Siren Speakers, Bumper Recess Mtd.
24" Exterior Chrome Grab Handles w/Integrated Led Strips

INTERIOR:

Driver's Pos. - Highback Air-Ride Suspension, HO Bostrom Sierra-50 Seat.
Officer's Pos. - Fixed Mounting - HO Bostrom - Tanker 300CT
Two (2) Rear Facing Fixed Bottom SCBA, HO Bostrom - Tanker 300CT
LED Cab Interior Lighting
Overhead Mounted SPS Panel - EsKey
57,600 BTU Heater Centered Over Windshield
45,000 BTU Air Conditioning with Heater - Single Condenser
36,000 BTU Supplemental Heater

PUMP:

47" Wide Side Mount Pump Enclosure
Hale, "DSD" 1500GPM Pump
1000 Gallon Polypropylene T-Tank
Left/Right 6.0" Steamers
One (1) 2.5" Left Side Intake
Two (2) Left and One (1) Right Side 2.5" Discharges
Right Side 3.0" Discharges
Right Side 2.5" Rear Discharge
1.5" Front Jumpline
3" Piping to Deluge Riser
3.0" Tank to Pump Piping
Crosslays, (2) Beds, Double Stacked 1.5" NST / 1.5" NST

BODY:

156ft³ Storage Compartment/ 72ft³ Hosebed
Hosebed - 63" Above Bumper
NFPA Through Tank Ladder Compartment
Roll-up, Satin Anodized Doors
Seven (7) SCBA Storage Compartments

LIGHTING:

Whelen ICC and Head/Tail/Brake Lighting
Whelen LED Warning Light Package

OPTIONAL EQUIPMENT

Center Hosewell w/Cover
1.5" Front Jumphines
Front 22.5"x9.0" Front Aluminum Wheels
Inner and Outer 22.5"x8.25" Rear Aluminum Wheels
40 Amp ProMariner Battery Charger
Kussmaul 20 AMP - 120v - Super Auto Eject

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

VIN

www.firetruck.com



HME, Incorporated - Wyoming