



VEHICLE DESCRIPTION

HME MiniEvo Ford F-550 SuperDuty Crew Cab XL 4x4 4-Door Chassis

19,500# GVWR • 1500 GPM Side Mount Pump • 300 Gallon Water Tank • Stainless Body 22983

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

DRIVETRAIN:

Powerstroke 6.7l V-8 OHV Turbo Diesel Engine
320 Amp Dual Alternator
750 Amp, 78 Amp Hours (Ah) Dual Batteries w/ Run Down Protection
6-Speed Electronic Selectshift Automatic Transmission
Part-Time 4-Wheel Drive w/ Manual Transfer Case Shift and Manual Locking Hubs
4-Wheel Disc Brakes with Front and Rear Vented Discs
Limited Slip Differential, Driveline Traction Control
4.88 Axle Ratio
Stainless Steel Exhaust
Front and Rear 19.5" X 6.00" Argent Steel Wheels

SAFETY:

Dual Airbags, Passenger Side Front-Impact Airbag, Seat Mounted Side-Impact Airbags, Curtain 1st and 2nd Row Overhead Airbags
Securilock Immobilizer, Panic Alarm, Security System

EXTERIOR:

Side Impact Beams, Fully Galvanized Steel Body Material
Power Remote, Heated, Convex Spotter Folding Manual Extendable Trailer Outside Mirrors with Turn Signal Indicators
Front Chrome Bumper with Front Tow Hooks
Aero-Composite Halogen Headlamps
Stainless Steel Cab Entrance Bars and Grille Guard
Additional Exterior Lights Include Cab Clearance Lights, Underhood Light, Remote Activated Perimeter/Approach Lights

INTERIOR:

Dual Airbags, Passenger Side Front-Impact Airbag, Seat Mounted Side-Impact Airbags, Curtain 1st and 2nd Row Overhead Airbags
Securilock Immobilizer, Panic Alarm, Security System
Cloth Headliner, Vinyl/Rubber Floor Covering, Chrome Interior Accent

FLEET OPTIONS:

XL Decor Group
Ambulance Prep Package

PUMP:

24" Side Mount Pump Enclosure
Midship, Hale "DSD", 1500 GPM Pump
Mechanical Seal
Intake and Discharge Anodes
Class 1 Master Drain
Right/Left Side 6" Steamer Inlets / Left Side 2.5" Inlet
2.5" Left Side and 3.0" Right Side Discharges
4.0" Right Side Rear Discharge
Two (2) 1.5" Double Stack Crosslays
3.0" Tank to Pump with 3.0" Ball Valve
300 Gallon T-Tank
8" x 8" Tank Fill Tower with 4" Vent
FRC Tank Level Gauge and In-Control Pressure Governor
2 1/2" Line Pressure Gauge

BODY:

Brushed Stainless Steel Body
Painted Roll-up Doors
139ft³ of Compartment Space
Hosebed with 40ft³ of Storage
R/S Compartment Top Ladder Storage: 8'-Roof, 8'Attic, 14-2 Section
L/S Compartment Top Two (2) 9'Hard Suction Storage
Compartment Shelving: Six (6) Deep and One (1) Shallow

LIGHTING:

Whelen LED Justice Light Bar
Whelen LED Stop/Tail/Turn/Backup Lighting

OPTIONAL EQUIPMENT

Sample TEXT

Ford Standard Driver – SCBA Officer – 3 Rear SCBA Crew Seats
40 Amp ProMariner Battery Charger
Kussmaul 20 AMP, 120v, Super Auto Eject
FRC "Turbo Foam" Class A Foam System
Foam System Outlets:Two (2) 1-1/2" Crosslays, Left Side 2-1/2" Discharge, Right Side 3" Discharge
15 Gallon Foam Tank
Upgraded Rear Folding Steps with LED Lighting
Worden Wheel Chocks
Upgraded Ford Console Options: Cup Holders, Dual Port USB Ports
Warn 9500 lbs Winch
Whelen M4 Series Model # M4V2R – Brush Guard Mounted
Whelen M4 Series Model # M4V2R – Forward of Wheelwell
Whelen M4 Series Model # M4V2R – Rear Upper Level Warning
Whelen M4 Series Model # M4V2R – Rear Lower Level Warning

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

VIN

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN



WWW.FIRETRUCKS.COM

WWW.FIRETRUCKS.COM