



VEHICLE DESCRIPTION

HME MiniEvo Dodge Ram 5500 4x4 4 Door Crew Cab
19,500# GVWR • 1500 GPM Side Mount Pump • 300 Gallon Water Tank • Stainless Body 23041

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

DRIVETRAIN:

Cummins 6.7L I6 OHV Turbo Diesel Engine
220 Amp Dual Alternator
730 Amp Battery w/ Run Down Protection
6 - Speed Electronic Sequential Shift Control Auto Trans w/ OD, Lock-Up, Driver Selection
Engine/Trans Cooler
Part-Time Four-Wheel Drive With Manual Transfer Case Shift, Auto Locking Hubs
Limited Slip Differential, ABS & Driveline Traction Control, PTO Provisions
4-wheel Disc Brakes
Front and Rear 19.5" x 6.00" Polished Aluminum Wheels
225/70R 19.5 tires

SAFETY:

4-wheel Anti-lock Braking System, Dual Airbags, Seat Mounted Driver and Passenger Side-Impact Airbags, Airbag Occupancy Sensor, Sentry Key Immobilizer, Panic Alarm

EXTERIOR:

1 Skid Plate, Black Fender Flares, Black Door Handles, Chrome Grille, 4 doors, Dual Power Remote Heated Manual Extendable Trailer Mirrors, Front Chrome Bumper with Front Tow Hooks, Remote Activated Perimeter/Approach Lights, Chrome Tubular Side Steps

INTERIOR:

6 Person Capacity, 4-way Adjustable Driver/Passenger Seats, Full Folding Rear Bench Seat with Fold Up Cushion, 3 Adjustable Rear Head Restraints, Vinyl Faced Front Seats with Vinyl Back Material, Vinyl Face Rear Seats with Carpet Back Material, Full Cloth Headliner, Full Vinyl/Rubber Floor Covering, Deluxe Sound Insulation

FLEET OPTIONS:

Chrome Appearance Group, HD Front Suspension Group, Heavy Duty Snow Plow Prep Group, Ambulance Prep Package

PUMP:

24" Side Mount Pump Enclosure
Midship, Hale "DSD", 1500 GPM Pump
Mechanical Seal
Intake and Discharge Anodes
Class 1 Master Drain
Right/Left Side 6" Steamer Inlets / Left Side 2.5" Inlet
2.5" Left Side and 3.0" Right Side Discharges
4.0" Right Side Rear Discharge
Two (2) 1.5" Double Stack Crosslays
3.0" Tank to Pump with 3.0" Ball Valve
300 Gallon T - Tank
8" x 8" Tank Fill Tower with 4" Vent
FRC Tank Level Gauge and In - Control Pressure Governor
2 1/2" Line Pressure Gauge

BODY:

Stainless Steel Body
Painted Roll - up Doors
139ft³ of Compartment Space
40ft³ of Hosebed Storage
R/S Compartment Top Ladder Storage: 8' - Roof, 8'Attic, 14 - 2 Section
L/S Compartment Top Two (2) 9'Hard Suction Storage
Compartment Shelving: Six (6) Deep and One (1) Shallow

LIGHTING:

Whelen LED Justice Light Bar
Whelen LED Stop/Tail/Turn/Backup Lighting
Whelen LED Warning Light Package

OPTIONAL EQUIPMENT

40 Amp ProMariner Battery Charger
Kussmaul 20 AMP, 120v, Super Auto Eject
FRC "Turbo Foam" Class A Foam System
Foam System Outlets:Two (2) 1 - 1/2" Crosslays, Left Side 2 - 1/2" Discharge, Right Side 3" Discharge
15 Gallon Foam Tank
Upgraded Rear Folding Steps with LED Lighting
Worden Wheel Chocks

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

VIN

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

