



VEHICLE DESCRIPTION

HME CommFox International 7400 4x2 4-Door Chassis

35,000# GVWR • 1250 GPM Side Mount Pump • 1000 Gallon Water Tank • Stainless Body 23046

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

DRIVE TRAIN:

Cummins L9, SCR, 330HP Engine
320 Amp Leece-Neville Alternator
Allison 3000 EVS 5 Spd Transmission
4-Wheel S-Cam Brakes

EXTERIOR:

Heated Moto Mirrors
Goodyear 12R22.5 Tires
Single Color Paint - Red

INTERIOR:

Deluxe Cab Interior Trim
Air Ride Driver's Seat
Front Passenger Non-air Seat
(3) Three individual rear seats

PUMP:

47" Side Mount Pump Enclosure
Midship, Hale "Q-Flo Plus", 1250 GPM Pump
Mechanical Seal
Intake and Discharge Anodes
Class 1 Master Drain
Right/Left Side 6" Steamer Inlets / Right Side Includes Strainer
Left Side 2.5" Intake
(2) Two Left Side 2.5" Discharges
2.5" Right Side Forward Discharge & 3" Right Side Rear Discharge
2.5" Right Side Rear Pre-Connect
(2) Two 1.5" Double Stack Crosslays
3.0" Tank to Pump with 3.0" Ball Valve
1000 Gallon T-Tank
10" x 14" Tank Fill Tower with 4" Vent
FRC Tank Level Gauge and In-Control Pressure Governor
2.5" Line Pressure Gauge

BODY:

Painted Stainless Steel Body
Satin Anodized Roll-up Doors
156ft³ of Compartment Space
63" High Hosebed with 72Ft³ of Storage
R/S Compartment Top Ladder Storage: 14'-Roof, 10' Attic, 24' - 2 Section
Rear Hard Suction Storage Compartment - Three (3) 6" Compartment Shelving:

LIGHTING:

Whelen Lighting Package

OPTIONAL EQUIPMENT

Black Rubber Mud Flaps - Front
Fuel Tank Cover
Battery Compartment Cover
22.5" Front Polished Aluminum Wheels
22.5" Rear Outer Polished Aluminum Wheels
Dual Stutter Tone Air Horns
40 Amp ProMariner Battery Charger
Body Installed Rubrail with LED Strip lighting

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

VIN

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN



WWW.FIRETRUCKS.COM

WWW.FIRETRUCKS.COM