



## VEHICLE DESCRIPTION

### HME 1871 SFO 4x2 4-Door Custom Chassis

45,740lbs GVWR • 1500 GPM Side Mount Pump • 1000 Gallon Water Tank • Stainless Body w/Painted Accents 23076

## OPTIONAL EQUIPMENT

Center Hosewell  
1.5" Front Jumpline  
Front 22.5"x9.0" Front Aluminum Wheels  
Inner and Outer 22.5"x8.25" Rear Aluminum Wheels  
Wheel Bright Finish & Protection

## STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

### DRIVETRAIN:

Cummins ISL9 370hp EPA13 Engine  
Allison 3000EVS Automatic Transmission  
Engine Brake  
S-Cam Front and Rear Brakes  
Goodyear 315/80R22.5-20PR (J) Front - G291 - 18,180# Front Tires  
Goodyear 12R22.5-16PR (H) Rear M&S - G182 - 27,000# Rear Tires  
270 Amp Leece-Neville Alternator  
50 Gallon Fuel Tank

### EXTERIOR:

Four (4) Door Custom SFO-MFD Cab with 12" Raised Roof  
18,740LBS GAWR Front Axle  
27,000LBS GAWR Rear Axle  
3-Dimensional Stainless Front Grille -SFO  
Smooth Chrome Htd & Remote Controlled Moto-Mirror w/Convex  
Cab Ground Lights - LED Strip Lights  
21" Front Bumper Extension / Front Tow hooks  
Dual Stutter Tone Air Horns - Bumper Recessed  
Whelen Electronic Siren - Model 295SLSA1  
Cast Products Siren Speakers, Bumper Recessed  
Bright Anodized Chrome Grab Handles

### INTERIOR:

Driver's - Highback Air-Ride Suspension, HO Bostrom Sierra - 50 ABTS  
Officer's- Fixed Mounting - HO Bostrom - Tanker 300CT - ABTS  
Two (2) Rear Facing Fixed Bottom SCBA, HO Bostrom - Tanker 300CT  
LED Cab Interior Lighting  
Over Head Mounted SPS Panel - EsKey  
Apparatus Base Digital Electrical System - Class1 EsKey  
45,000 BTU Air Conditioning with Heater - Single Condenser  
36,000 BTU Supplemental Heater

### PUMP:

47" Side Mount Pump Enclosure  
Hale, "DSD" 1500GPM Pump  
Left/Right 6.0" Steamers  
One (1) 2.5" Left Side Intake  
Two (2) Left and Two (2) Right Side 2.5" Discharges  
1.5" Front Jumpline w/air blow out  
3" Piping to Deluge Riser  
Crosslays, (2) Beds, Double Stacked 1.5" NST / 1.5" NST  
1000 Gallon Polypropylene T-Tank  
3.0" Tank to Pump Piping w/3"air operated valve

### BODY:

156ft<sup>3</sup> Storage Compartment/ 72ft<sup>3</sup> Hosebed  
Hosebed - 63" Above Bumper  
Through Tank Ladder Compartment  
L/S, R/S Hinged Flush Mount Double Pan Stainless Doors  
RR1 Slam Door  
Compartment Shelving and Toolboards  
L/S, R/S SCBA Storage Tubes  
NFPA Ladder Group

### LIGHTING:

Whelen Freedom Lightbar, and Head/Tail/Sides/Brake Lighting  
Federal Signal Turn Signals  
Whelen LED Warning Light Package

## SOLD TO

Stock Inventory

## METHOD OF TRANSPORTATION

Drive-Away

## FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

## VIN

TOTAL

SEE A SALES REPRESENTATIVE

www.firetruck.com



HME, Incorporated - Wyoming