



## VEHICLE DESCRIPTION

HME 1871W SilverFox Urban 4x2 4-Door Custom Chassis  
42,740lbs GVWR • 1500 GPM Side Mount Pump • 500 Gallon Water Tank • Stainless Body 23110

## OPTIONAL EQUIPMENT

Center Hosewell  
1.5" Front Jumphines  
Front 22.5"x9.0" Front Aluminum Wheels  
Outer 22.5"x8.25" Rear Aluminum Wheels  
40 Amp ProMariner Battery Charger  
Kussmaul 20 AMP - 120v - Super Auto Eject  
Two Tone Paint Scheme  
45° Cramp Angle

## STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

### DRIVETRAIN:

Cummins ISL9 400hp EPA17 Engine  
Allison 3000EVS Automatic Transmission  
"Jacobs" Engine Brake  
S-Cam Front and Rear Brakes  
Goodyear 315/80R22.5-18PR (J) Front - G291 - 16,540# Front Tires  
Goodyear 11R22.5-16PR (H) Rear M&S - G182 - 24,000# Rear Tires  
270 Amp Leece-Neville Alternator  
50 Gallon Fuel Tank

### EXTERIOR:

Four (4) Door Custom 1871-W Cab with 12" Raised Roof  
18,740LBS GAWR Front Axle  
24,000LBS GAWR Rear Axle  
3-Dimensional Stainless Front Grille  
Heated and Remote Controlled Mekra Lang 400 Series w/ Lower Convex  
Cab Ground Lights - LED  
18" Front Bumper Extension / Front Tow Hooks  
Dual Stutter Tone Air Horns - Bumper Recessed  
Whelen Electronic Siren - Model 295SLSA1  
Cast Products Siren Speaker, Bumper Recessed Grab Handles

### INTERIOR:

Driver's Pos - Highback Air-Ride Suspension, HO Bostrom  
Officer's Pos - Split Head Rest, Fixed Mount, HO Bostrom  
Two (2) Fixed Bottom Rear Facing SCBA, HO Bostrom  
Two (2) Flip Bottom Forward Facing SCBA, HO Bostrom  
LED Cab Interior Lighting  
Dog House Mounted SPS Panel - EsKey  
Apparatus Base Digital Electrical System - Class1 EsKey  
46,000 BTU Air Conditioning with Heater - Single Condenser  
Floor Heat Driver-Officer-Crew Seats

### PUMP:

47" Side Mount Pump Enclosure  
Hale, "Q-Max" 1500GPM Pump  
Left/Right 6.0" Steamers  
One (1) 2.5" Left Side Intake  
Two (2) Left and One (1) Right Side 2.5" Discharges  
Right Side 3.0" Discharges  
Right Side 2.5" Rear Discharge  
3" Piping to Deluge Riser  
Crosslays, (2) Beds, Double Stacked 1.5" NST / 1.5" NST  
500 Gallon Polypropylene T-Tank  
3.0" Tank to Pump Piping

### BODY:

156ft<sup>3</sup> Storage Compartment/ 72ft<sup>3</sup> Hosebed  
51" High Hosebed  
Through Tank Ladder Compartment  
Roll-up, Satin Anodized Doors  
Compartment Shelving and Toolboards  
SCBA Storage  
NFPA Ladder Group

### LIGHTING:

Whelen ICC and Head/Tail/Brake Lighting  
Federal Signal Turn Signals  
Whelen LED Warning Light Package  
FRC Body Quartz Lighting

**TOTAL** SEE A SALES REPRESENTATIVE

## SOLD TO

Stock Inventory

## FINAL ASSEMBLY POINT

WYOMING, MICHIGAN

## METHOD OF TRANSPORTATION

Drive-Away  
VIN

www.firetruck.com



HME, Incorporated - Wyoming