



VEHICLE DESCRIPTION

HME MiniEvo Ram 5500 4x4 4 Door Crew Cab

19,500# GVWR • 1500 GPM Side Mount Pump • 300 Gallon Water Tank • Stainless Body 23283

STANDARD EQUIPMENT INCLUDED IN THE BASE VEHICLE

**DRIVETRAIN:**

Cummins 6.7L I6 OHV Turbo Diesel Engine  
220 Amp Dual Alternator  
6 Speed Electronic Sequential Shift Control Auto Trans w/ OD, Lock-Up, Driver Selection  
Engine/Trans Cooler  
Part-Time Four-Wheel Drive With Manual Transfer Case Shift, Auto Locking Hubs  
Limited Slip Differential, ABS & Driveline Traction Control, PTO Provisions  
4-wheel Disc Brakes  
Front and Rear 19.5" x 6.00" Polished Aluminum Wheels  
225/70R 19.5 AT Tires (All-Terrain)

**SAFETY:**

4-wheel Anti-lock Braking System, Dual Airbags, Seat Mounted Driver and Passenger Side-Impact Airbags, Airbag Occupancy Sensor, Sentry Key Immobilizer, Panic Alarm

**EXTERIOR:**

1 Skid Plate, Black Fender Flares, Black Door Handles, Chrome Grille, 4 doors, Dual Power Remote Heated Manual Extendable Trailer Mirrors, Front Chrome Bumper with Front Tow Hooks, Remote Activated Perimeter/Approach Lights, Chrome Tubular Side Steps

**INTERIOR:**

5 Person Capacity, 4-way Adjustable Driver/Passenger Seats, Full Folding Rear Bench Seat with Fold Up Cushion, 3 Adjustable Rear Head Restraints, Vinyl Faced Front Seats with Vinyl Back Material, Vinyl Face Rear Seats with Carpet Back Material, Full Cloth Headliner, Full Vinyl/Rubber Floor Covering, Deluxe Sound Insulation

**FLEET OPTIONS:**

Chrome Appearance Group, HD Front Suspension Group, Heavy Duty Snow Plow Prep Group, Ambulance Prep Package, Backup Camera

**PUMP:**

24" Side Mount Pump Enclosure  
Midship, Hale "DSD", 1500 GPM Pump  
FRC "Turbo Foam" Class A Foam System  
Foam System Outlets:Two (2) 1 - 1/2" Crosslays, Left Side 2 - 1/2" Discharge, Right Side 3" Discharge  
15 Gallon Foam Tank  
Mechanical Seal  
Intake and Discharge Anodes  
Class 1 Master Drain  
Right/Left Side 6" Steamer Inlets / Left Side 2.5" Inlet  
2.5" Left Side and 3.0" Right Side Discharges  
4.0" Right Side Rear Discharge  
Two (2) 1.5" Double Stack Crosslays  
3.0" Tank to Pump with 3.0" Ball Valve  
300 Gallon T - Tank  
8" x 8" Tank Fill Tower with 4" Vent  
FRC Tank Level Gauge and In - Control Pressure Governor 2 1/2" Line Pressure Gauge

**BODY:**

Stainless Steel Body  
Painted Roll - up Doors  
139ft<sup>2</sup> of Compartment Space  
Hosebed with 40ft<sup>2</sup> of Storage  
R/S Compartment Top Ladder Storage: 8' - Roof, 8'Attic, 14 - 2 Section  
L/S Compartment Top Two (2) 9'Hard Suction Storage  
Compartment Shelving: Six (6) Deep and One (1) Shallow

**LIGHTING:**

Whelen LED Justice Light Bar  
Whelen LED Stop/Tail/Turn/Backup Lighting  
Whelen LED Warning Light Package

OPTIONAL EQUIPMENT

40 Amp ProMariner Battery Charger  
Kussmaul 20 AMP, 120v, Super Auto Eject  
Upgraded Rear Folding Steps with LED Lighting  
Worden Wheel Chocks

TOTAL SEE A SALES REPRESENTATIVE

SOLD TO

Stock Inventory

METHOD OF TRANSPORTATION

Drive-Away

VIN

FINAL ASSEMBLY POINT

WYOMING, MICHIGAN



WWW.FIRETRUCKS.COM

WWW.FIRETRUCKS.COM